



## Hotmelt Applicator



# TEC 810

The **TEC 810-12** brings a new level of performance and reliability to the mid range industrial glue gun section of the market.

The **TEC 810-12** has been designed for continuous industrial use. Built in the UK to the highest standard with the goal of having the highest performing glue gun in its class.

The **TEC 810-12** features a highly efficient melt chamber which gives a warm up time of only 2 to 3 minutes, with a glue delivery rate in excess of 2 kilos an hour (depending upon glue formulation).

The temperature is accurately controlled by a preset thermostat. These can be easily changed to adjust the gun temperature for the different types of Hotmelt and Lowmelt adhesives available.

The **TEC 810-12** is exceptionally comfortable and easy to use with a full hand lever trigger, narrow profile handle and soft feel grip. The trigger can also be adjusted to suit different sized hands.

The guns thin profile improves access and visibility and the smooth nose section is easy to clean. With illuminated on/off switch and a detachable base stand that also includes a nozzle spanner and stores the trigger stop adjustment screw.

The **TEC 810-12** is the only choice for an industrial mid range glue gun as it meets all requirements in this section of the market.

Covered by a one year guarantee the **TEC 810-12** complies with worldwide industrial and electrical safety standards.



---

## ADVANCED FEATURES

Pic. 1: Illuminated on-off switch & detachable stand incorporating nozzle spanner



Pic. 2: Thin profile for easy visual positioning of the molten adhesive



Pic. 3: Narrow profile handle with soft feel grip & full hand lever trigger & adjustable trigger stroke screw.



Pic. 4: Easy change temperature thermostats & rubber nozzle shroud for extra safety.



## SPECIFICATION:

Voltage: 230 V - 50-60HZ

Heater: 250 Watt high performance stainless steel cartridge

Temperaturüberwachung: Pre-set Thermostats (Fitted with 195oc) with safety thermal fuse other temperature easy change thermastats available

Power cable: 2m three core rubber sheathed cable fitted with European plug, Australian, Swiss & USA versions available

Melt rate: Up to 2kilo/hr depending on adhesive & temperature

Adhesive size: TECBOND 12mm glue sticks

Grüner Weg 45-51  
58644 Iserlohn

Postfach 71 65  
D-58609 Iserlohn

Fax +49-2371-95999-9  
Tel +49-2371-95999-0